

**Allgemeine Informationen**  
Allgemeine Rohrmass-Tabelle der  
Wasserversorgungs-Materialien

**Informations générales**  
Tableau des dimensions de tube  
pour les matériels d'approvision-  
nement d'eau

**Informazioni generali**  
Tabella generale della massa  
grezza dei materiali di approv-  
vigionamento d'acqua

DN	NW [Zoll]	Gussrohr Schraub- muffen alt AD [mm]	Gussrohr SRM-Rohr DIN 28601 AD [mm]	Gussrohr SRM-Rohr Von Roll AD [mm]	Gussrohr Steckmuffen EN 545 AD [mm]	Gussrohr mit PE- Umhüllung AD [mm]	Steck- muffen FZM/ZMU AD [mm]	Stahlrohr AD [mm]	Stahlrohr EN 10297-1 AD [mm]	PE-Druck- rohr DIN 8074 AD [mm]	Eternit- Rohr ND 10/18 AD [mm]	Eternit- Rohr ND 16/24 AD [mm]
15	½"		25					21 – 21,5	21,3 ±0.5	20 +0.3		
20	¾"		33					26 – 27	26,9 ±0.5	25 +0.3		
25	1"		39					33 – 34	33,7 ±0.5	32 +0.3		
32	1¼"	42 – 43	46					42 – 43	42,4 ±0.5	40 +0.4		
40	1 ½"	51 – 53	56 +2.1/-2.6	52 +2/-1	56 +1/-1.2			46 – 49	48,3 ±0.5	50 +0.5		
50	2"	62 – 64	66	63 +2/-1	66 +1/-1.2			56 – 61	60,3 ±0.6	63 +0.6		
60		72 – 74	77					70 – 71				
65	2½"		82		82 +1/-1.2			72 – 76	76,1 ±0.8	75 +0.7		
70		83 – 85	87	84 +2/-1				77 – 79				
75	3"	88 – 91						82 – 84				
80		94 – 96	98 +2.2/-2.7	95 +2/-1	98 +1/-2.7		108	88 – 89	88,9 ±0.9	90 +0.9		104
90		104 – 108	108					97 – 102				
100	4"	114 – 116	118 +2.2/-2.8	116 +2/-1	118 +1/-2.8	121.6 +2.2/-2.8	128	107 – 109	108,0 ±1.1 114,3 ±1.1	110 +1.0 125 +1.2		128
110		123 – 125										
120		134 – 137										
125	5"	140 – 143	144 +2.3/-2.8	141 +2 /-1	144 +1/-2.8	148 +2.3/-2.8	154	132 – 134	133,0 ±1.3 139,7 ±1.4	140 +1.3		157
135		150 – 153										
150	6"	166 – 169	170 +2.3/-2.9	168 +2 /-1	170 +1/-2.9	174 +2.3/-2.9	180	157 – 160	159,0 ±1.6 168,3 ±1.7	160 +1.5 180 +1.7		186
165		180 – 184										
175		191 – 194	196					183 – 191				
180		198 – 200										
190		208 – 211										
200	8"	218 – 222	222 +2.4/-3.0	220 +2/-1	222 +1/-3.0	226 +2.4/-3.0	232	211 – 216	200,0 +2.0 219,1 ±2.2	200 +1.8 225 +2.1	236	244
225		244 – 247	248					241		250 +2.3		
250	10"	268 – 273	274 +2.5/-3.1	273 +2.5/-1.5	274 +1/-3.1		284	267	267,0 ±2.7 273,0 ±2.7	280 +2.6	292	304
275		297 – 300	300					292				
300	12"	322 – 325	326 +2.6/-3.3	324 +2.5/-1.5	326 +1/-3.3	330.4 +2.6/-3.3	336	316	323,9 ±3.2	315 +2.9 355 +3.2	350	364
315			341									
325		348 – 352	352					343				
350	14"	376 – 379	378 +2.7/-3.4	376 +2.5/-1.5	378 +1/-3.4		388	368	355,6 ±3.6 368,0 ±3.7	355 +3.2 400 +3.6	410	426
375			403					394				
400	16"	426 – 430	429 +2.8/-3.5	427 +2.5/-1.5	429 +1/-3.5	433.4 +2.8/-3.5	439	419	406.4 ±4.1 419.0 ±4.2	400 +3.6 450 +3.8	468	488
450	18"				480 +1/-3.5							
500	20"				532 +1/-3.8				508.0 ±5.1			